ViewSonic® VA702 LCD Monitor

17" A SERIES LCD DISPLAY



Attractive Styling in a Super-slim LCD.

The ViewSonic VA702 LCD display not only brings images to life with vivid colour and outstanding realism. Its stylish design is also sure to catch your eye. The fold-up base makes wall mounting a breeze, letting you reclaim long-lost desk space. Delivering ViewSonic's renowned image quality, the VA702 enhances your viewing comfort with high brightness and progressive styling. Get the LCD display with perfect looks - the ViewSonic VA702!

Fun, Style and Comfort

---**;** UltraBrite™ technology

UltraBrite[™] technology enables optimised viewing of video and graphics applications. Games, TV and DVDs come alive with rich, saturated colour and vivid contrast. Precise definition and photorealistic image quality boost 3-D video and professional graphics.

---> 1280 x 1024 optimum resolution

-- OSD/power lock function

When activated, the user-controlled OSD/power lock function prevents changes to monitor settings, maintaining an optimised image.

The compact base folds up 90° for VESA-compliant wall mounting, making conversion between desktop and wall mount applications easy.

---->OnView controls including ViewMatch technology

Screen adjustments are made via an on-screen menu using simple controls. This user-friendly control system allows easy adjustments of image quality, size, position and geometry for optimal viewing.

... AutoTune™ function

Provides the best image by monitoring signals from the computer and automatically optimising the monitor settings.

--- ViewSonic Wizard

User-friendly Wizard software automates the setup process to deliver optimized screen performance.

---> TCO'03 and Energy certified

This LCD display complies with one of the world's strictest standards for low emissions, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.

-- sRGB colour management

For a closer match of image display to print outs.

----> PC and Mac® compatible



the choice of professionals

Clear Choice

ViewSonic® VA702 LCD Monitor

17" A SERIES LCD DISPLAY





- 1. One-touch buttons control all major functions
- 2. Space-saving slim-line design is only 6.1cm thick
- 3. Ultra compact, attractive design with slim bezel
- 4. Flat folding base for easy wall mounting




Available colour: Black/Silver dual tone

17" COLOUR LCD DISPLAY WITH STYLISH SLIM BEZEL DESIGN

17 COLOUN LCD DIS	DI LAT WITH STILLISH SL	IIVI DLZLL DLJIQIV
LCD PANEL	Type Display Area Pixel Pitch Optimum Resolution Pixel Clock Contrast Ratio Viewing Angles Response Time Colour Support Brightness Panel Surface	17" Colour TFT Active Matrix SXGA LCD, TN Technology 33.8cm horizontal x 27.0cm vertical, 43.2cm diagonal 0.264mm 1280 x 1024 135MHz 500:1 (typ.) 140° horizontal, 130° vertical @10:1 160° horizontal, 155° vertical @5:1 8ms (typ.) 16.2M colours (6-bit + 2-bit FRC) 300 cd/m² (typ.) Anti-glare 3H
VIDEO INPUT	Analogue Frequency Synchronisation	RGB Analogue (75 ohms, 0.7 Vp-p) F _h : 30-82kHz, F _V : 50-85Hz H/V separated (TTL)
COMPATIBILITY	PC Mac®1	VGA up to 1280 x 1024 @ 75Hz (non interlaced) Power Mac™ up to 1152 x 870 @ 75Hz
CONNECTOR	Signal Power	15-pin mini D-Sub (detachable cable) 3-pin AC plug (CEE22)
POWER	Voltage Consumption	AC 100-240V, 50-60Hz (auto-switch), internal power supply <35W (typ.), <1W in suspend mode
ERGONOMICS	Tilt	Down 5°, Up 20°
USER CONTROLS	Physical OSD	Power on/off, menu, up, down, select Auto Image Adjust, Contrast, Brightness, Colour Adjust [sRGB, 9300K, 6500K (default), 5400K, User (R, G, B)], Information [Mode, Model Number, Serial Number, Website], Manual Image Adjust [H. Size, H./V. Position, Fine Tune, Sharpness, Scaling], Setup Menu [Language (English, French, German, Italian, Spanish, Finnish, Japanese, Simplified and Traditional Chinese), Resolution Notice, OSD Position, OSD Timeout, OSD Background], Memory Recall
OPERATING CONDITIONS	Temperature Humidity	0–40°C 10–90% (non-condensing)
DIMENSIONS	Physical	378 x 374 x 196 (W x H x D in mm)
WEIGHT	Net	4.5kg
REGULATIONS		TCO'03, TÜV/GS, TÜV/Ergo, ISO13406-2 (class 2), UL, c-UL, CB, CE, FCC-B, CCC, PSB, TÜV-S, ENERGY, EPA EnergyStar, NOM, GOST-R, (SASO), BSMI, (C-TICK), IRAM, ICES-B
POWER MANAGEMENT		Meets TCO, ENERGY STAR and ENERGY standards.
PACKAGE CONTENTS		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
WARRANTY		Please see:







the choice of professionals

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution

ViewSonic House Fleming Way, Crawley West Sussex, RH10 9GA United Kingdom

ViewSonic Europe Limited/UK

Tel: +44 (0) 12 93 64 39 00 Fax: +44 (0) 12 93 64 39 10 ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A 47877 Willich Germany

Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10 ViewSonic France

Parc des Barbanniers 1 allée des Bas Tilliers 92230 Gennevilliers France

Tel: +33 (0) 1 41 47 49 00 Fax: +33 (0) 1 41 47 49 10 ViewSonic Corporation

381 Brea Canyon Road Walnut California 91789-0708 USA

Tel: +1 909 869 7976 Fax: +1 909 869 7958 ViewSonic Belux ViewSonic Denmark ViewSonic Finland ViewSonic Italy ViewSonic MEA ViewSonic Netherlands ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27 Tel: +45 70 22 11 71 Tel: +358 (0)9 5406 4070 Tel: +39 02 73 95 50 22

Tel: +971 (0) 4 88 11 871 Tel: +31 (0)20 491 9254 Tel: +47 (0) 22 88 17 60 Tel: +34 (0) 91 63 05 339 Tel: +46 (0) 8 50 71 30 00

1 May require optional Mac adapter. Specifications subject to change without notice. Selection, offers and programmes may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright o 2006 ViewSonic Corporation. All rights reserved. VS VA702-02 09/06-UK