

VA1903wb

**19" WIDESCREEN LCD
MONITOR VALUE SERIES
WITH 5MS VIDEO RESPONSE TIME**

Widescreen enjoyment for all

ViewSonic's VA1903wb LCD brings the enjoyment of panoramic widescreen to the masses. The 16:10 wide aspect ratio and high 1440 x 900 resolution provide AMPLE SPACE FOR MULTIPLE DOCUMENT WINDOWS or side-by-side full page layouts. Thanks to a SUPER-FAST 5MS response time together with 300cd/m² brightness levels and high 700:1 contrast, you get to enjoy superior blur-free clarity, amazing colour and stunning brightness. The VA1903wb delivers on ViewSonic's tradition of BRILLIANT IMAGE QUALITY AND RELIABLE PERFORMANCE all at an attractive price. It's the easy choice for gamers, home/small office users and corporate professionals.

It's not just another widescreen LCD. It's a ViewSonic.



LIFESTYLE ENJOYMENT WORKPLACE PRODUCTIVITY

- > **Super fast 5ms video response delivers superior picture clarity**
- > **Full 19" viewable widescreen**
Displays a full, flat 19" viewable widescreen area with crisp detail and fully saturated colour.
- > **1440 x 900 native resolution**
Incredible image detail for sharp text and graphics.
- > **High brightness and contrast**
300cd/m² brightness (typ.) and 700:1 contrast ratio (typ.) for rich, detailed images.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**
Prevents changes to monitor settings and maintains an optimized image.
- > **OnView® controls for superior screen adjustability**
Screen adjustments can be made precisely via an easy-to-use on-screen menu.
- > **Integrated power supply**
- > **ViewSonic Wizard included**
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > **PC and Mac® compatible**
- > **TCO'03 and Energy Star® qualified**



VA1903wb

19" WIDESCREEN LCD MONITOR VALUE SERIES WITH 5MS VIDEO RESPONSE



LCD	Type	19" Wide TN colour TFT active matrix WXGA+ LCD	
	Display Area	41.0cm horizontal x 25.6cm vertical, 48.3cm diagonal	
	Pixel Pitch	0.285mm	
	Optimum Resolution	1440 x 900@60Hz	
	Pixel Clock	140MHz	
	Contrast Ratio	700:1 (typ.)	
	Viewing Angle	150° horizontal, 140° vertical (at 10:1) 160° horizontal, 160° vertical (at 5:1)	
	Response Time	5ms (off-on-off) (typ.)	
	Colour Support	16.2M colours (6-bit+2-bit FRC)	
	Light Source	Long life, 50000 (min.)	
	Brightness	300cd/m ²	
Panel Surface	Anti-glare (3H)		
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)	
	Frequency	F _H : 24–82kHz, F _V : 50–75Hz	
	Synchronisation	H/V separate (TTL)	
COMPATIBILITY	PC	VGA up to 1440 x 900 non-interlaced	
	Mac ¹	Power Mac™ G3/G4/G5 up to 1440 x 900 non-interlaced	
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)	
	Power	3-pin AC plug (CEE22)	
POWER	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply	
	Consumption	34 watt (typ.), <1 watt in power save mode	
ERGONOMICS	Tilt	Down 5°, Up 20°	
CONTROLS	Basic	Power, menu [1], up, down, select [2]	
	OSD	Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall	
OPERATING CONDITIONS	Temperature	0°C–40°C	
	Humidity	10%–90% (non-condensation)	
DIMENSIONS	(W x H x D mm)	448 x 404 x 210 (with stand) 448 x 318 x 63 (without stand) 520 x 473 x 158 (packaging)	
	WEIGHT	Net	4.7kg (with stand)
		Gross	6.0kg
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CE, CB, GOST-R, Hygienic (20 copies), UL, cUL, FCC-B (ICES), ICES-003B, NOM, SASO, ENERGY, Energy Star, C-Tick, KTL/MIC, BSMI, PSB, MPR II, TÜV-S, CCC, VCCI, WEEE, RoHS	
POWER MANAGEMENT		TCO'03 and Energy Star standards	
SECURITY		Kensington security port	
WALL MOUNT		VESA FDMI 100mm x 100mm	
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)	
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK

ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic Italy

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +39 02 73 95 50 22
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter.