Maximum Impact at Minimum Cost — Enduringly Economical!



Low Cost of Ownership Reduce your operating expenses with the bSure's unique long-life lamps,

which last up to three times longer!

Extend Lamp Life SmartSave[™] extends valuable lamp life by automatically switching off the

projector after a user-defined interval.

Ultra-Quiet Philips' innovative PAS™ system dramatically reduces fan noise to an ultra-

quiet 27dB.

Anti-Theft Protection SecurityMax[™] theft deterrent software and integrated Kensington lock

protect your investment in any environment.

Easy to Use SmartSet[™] utilizes advanced digital architecture to instantly adjust all display

parameters for optimal performance and versatility.

Future Proof Featuring HDTVReady™ the bSure Series is fully compatible with future

digital television standards.

Now Even Brighter The bSure Series delivers maximum impact with 1500 ANSI lumens light output.











| Model Name | bSure SV2 | bSure XG2 | | | |
|---|---|--|--|--|--|
| Model Number | LC3132 | LC3142 | | | |
| LCD | 3x 0.7" high-temperature poly | silicon active matrix LCD panels | | | |
| Native Resolution Number of pixels Brightness Contrast | SVGA (800x600) XGA (1024x768) 3x 480,000 3x 786,432 1500 ANSI lumens 300:1 | | | | |
| Fan Noise | 27 dB | 29 dB | | | |
| Lamp Average Lifetime | 132 watt UHP™ lamp 6000 hrs | 150 watt UHP™ lamp 3000 hrs | | | |
| Lens | F/1.8 - 2.2 | | | | |
| Input Compatibility Video | NTSC 3.58 4.43 PAL SECAM S-Video (Y/C) Component Video Input: YCbCr,YPbPr, RGB HDTV Compatible: (480p, 720p, 1080i) | | | | |
| Computer | Compatible with: VGA, SVGA, XGA, SXGA, Mac/PC Horizontal Scan Rate: 15 - 108 kHz Vertical Refresh Rate: 50 - 120 Hz Bandwidth: 140 MHz Display Data Channel: DDC 1/2B | | | | |
| Plug and Play Compatibility | Microsoft® Windows®, 95/98/ME/2000/XP compatible | | | | |
| Input Connectors Video | Component Video (R/Pr/Cr, G/Y, B/Pb/Cb: 3x RCA) 1x Composite Video (RCA) 1x S-Video (Y/C: mini-DIN) | | | | |
| Computer | 1x RGB Data (D15-pin) | | | | |
| Audio Video Data Speaker | Stereo Audio (2x RCA) 1x Stereo Audio (3.5 mm stereo jack) 6 watts | | | | |
| Mouse Control | USB (type A), PS/2 (mini-DIN) | | | | |
| Features | SecurityMax™ Theft protection SmartSet™ automatic image quality optimization SmartSave™ auto-standby mode helps extend lamp life ColorTracking™ provides superior colorimetry for Video display Digital Zoom and Digital Freeze Digital Keystone correction with FitScreen optimization Connect an external computer monitor using supplied Y-Cable | | | | |
| Physical Specification Product Dimensions Product Weight | (HxWxD) 4.25" x 9.25" x 13.2 | " (108 x 235 x 335 mm) (3.7 kg) | | | |
| Power consumption Operating Voltage Operation / Standby | 100 - 240 VA | AC, 50/60 Hz 210 watts / 5 watts | | | |
| Temperature Range Operational Storage | +41 to +95 °F -13 to +158 °F | (+5 to +35 °C) (-25 to +70 °C) | | | |
| FCC Rating | Cla | ss B | | | |
| Included Accessories | Compact Remote Control, Power Cord, Lens Cap Combined VGA-USB Cable (79" / 1.5m), Audio/Video cable (79" / 2m) Scart to RCA Adapter (audio/video), D15-pin Y-Cable CD-ROM User Guide (UK, D, F, E, PT, NL I) Quick Setup Card (UK, D, F, E, PT, NL, I) Warranty Card | | | | |
| Optional Accessorie | LCA3116 132 watt Replacemen | nt Lamp for bSure SV2 nt Lamp for bSure XG2 | | | |
| Madal Numban | 1/2122 | 1/21/13 | | | |



Key Features


- UHP[™] Long-life Lamp (up to 6,000 hours)
- · Low Cost of Ownership
- Ultra-Quiet only 27dB
- SecurityMax[™] Theft Protection

Projection Chart

| Image Diagonal size | | Projection Distance | | | |
|---------------------|----------|---------------------|----------|-----------|----------|
| | | Tele zoom | | Wide zoom | |
| [inch] | [meters] | [inch] | [meters] | [inch] | [meters] |
| 40 | 1.0 | 74 | 1.9 | 59 | 1.5 |
| 60 | 1.5 | 112 | 2.8 | 91 | 2.3 |
| 70 | 1.8 | 130 | 3.3 | 106 | 2.7 |
| 80 | 2.0 | 150 | 3.8 | 121 | 3.1 |
| 100 | 2.5 | 187 | 4.7 | 152 | 3.9 |
| 150 | 3.8 | 280 | 7.1 | 228 | 5.8 |
| 200 | 5.1 | 374 | 9.5 | 304 | 7.7 |
| 250 | 6.4 | 468 | 11.9 | 380 | 9.7 |

All values are estimates

Input Panel







Hassle-Free Service and Support

Philips' First Choice Warranty assures you that you'll always be ready to present even in case of equipment failure thanks to our toll-free technical support (1 year), 48-hour Roadside Assistance Program and 3-year Parts and Labor Warranty.**

INTERNET ADDRESS: http://www.philipsusa.com TECHNICAL SUPPORT: Toll Free 1-888-873-4672 SALES INFORMATION: Toll Free 1-888-327-3636

Philips Consumer Electronics 64 Perimeter Center East Atlanta, Georgia 30346

LC3142

Design and specifications are subject to change without notice. Printed in the U.S.A., ©2003 Philips Consumer Electronics Co., a Division of Philips Electronics North America Corp.

- st Available in the USA and Western Europe. Check with your dealer for similar coverage in other regions.
- ** Projector warranty is 3 years or 2500 hours, whichever comes first. Run time is kept by an internal clock. Warranty on internal projection lamp is 12 months.

All trademarks are property of their respective owners. CCM-150-2_3/03

Literature Order Number: bSure Series 2



Model Number

LC3132